## MAYNUFACTURE OF SEMICONDUCTOR DEVICE

## MANUFACTURE OF SEMICONDUCTOR DEVICE Patent Number: JP2129913 Publication date: 1990-05-18

Inventor(s): MOCHIZUKI KOJI; others: 01
Applicant(s): FUJITSU LTD

Requested Patent:

Application Number: JP19880282801 19881109

Priority Number(s):

IPC Classification: H01L21/205

EC Classification:
EC Classification:
Equivalents:

## Abstract

PURPOSE: To enable adsorption formation of excess-free Ga atomic layer by restraining taking-in of C atom which becomes impurity by adsorbing Ga atom mainly through TEG and by adsorbing lacking Ga atoms through TMG.

CONSTITUTION: When a Ga atomic layer is adsorbed to an atomic plane of a substrate, a Ga atom amount which does not cause Ga adsorption in excess of one atomic layer is adsorbed at first using triethylgallium(TEG) as a raw material. Then, lacking Ga atoms are adsorbed to one atomic layer at Ga atomic layer to complete a Ga layer of one atomic layer using trimethylgallium(TMG) as a raw material. Arsine is used as a raw material of As in the growth of GaAs, and As which is another element to constitute compound semiconductor is suppled. Adsorption formation of excess-free Ga atomic layer can be realized in this way.